

Advance Wireless Charger



Single Bay
Wireless
Charger



**DURA FORCE
PRO**

by **KYOCERA**



4 Bay
Wireless Charger

The AdvanceWireless Charger is a complete, self-contained wireless charging system. By placing the Kyocera DuraForce Pro phone into the charger cradle of the Advance Wireless Charger, it will implement a 5W wireless charging algorithm and will automatically adjust the charging power, based on the feedback from the phone. The AdvanceWireless Charger contains a custom controller for managing the charging protocol and functions.

FEATURES

- **Dimensions:**
 - Single Bay: 7.25" x 3.75" x 2.9"
 - 4 Bay: 14.5" x 3.75" x 2.9"
- **Weight:** 8 oz. $\pm 5\%$
- **Operating temperature:** -20°C to +50°C
- **Storage temperature:** -40°C to +85°C
- **Relative humidity:** 95% maximum non-condensing
- **Power supply:**
 - Single Bay
 - Input: 115VAC-230 VAC,
 - Output: 15VDC 800mA Cord: 6 ft 22 AWG x 2C, 90C
 - 4 Bay
 - Input: 115VAC-230 VAC,
 - Output: 15VDC 4A Cord: 6 ft 22 AWG x 2C, 90C
- **Charger Input:** 2.5 mm center positive:
 - Single Bay: 12VDC-24VDC $\pm 20\%$, 800mA
 - 4 Bay: 12VDC-24VDC $\pm 20\%$, 4A

INNOVATIVE ENGINEERING AND MANUFACTURING FOR OVER 25 YEARS

305-623-3939 | 1-800-881-8211 | isanchez@advancetec.com | www.AdvanceTec.com

